

- Materiaal: Roestvaststaal (A2)
- Schroefdraad: Metrisch


RVS

**Rond, open,
platkop en
gereduceerde
verzonken kop**




Standaard

Platkop



Gereduceerde verzonken kop



Artikelnummer platkop	Draad- soort	Gat- diameter +0,1/-0,0	Plaatdikte		Afmetingen			
			Min.	Max.	D ø	H ø	P	L
113531	M 4	6,0	0,5	3,0	5,9	9,0	1,1	11,0
113532			3,0	4,5				14,0
113533	M 5	7,0	0,5	3,0	6,9	10,0	1,1	13,0
113534			3,0	5,5				16,0
113535	M 6	9,0	0,5	3,0	8,9	12,0	1,6	16,0
113536			3,0	5,5				18,5
113537	M 8	11,0	0,5	3,0	10,9	15,0	1,6	17,5
113538			3,0	5,5				20,0
113539	M 10	13,0	0,5	3,0	12,9	16,0	2,1	19,0
113540			3,0	6,0				24,0

Artikelnummer gereduceerde verzonken kop	Draad- soort	Gat- diameter +0,1/-0,0	Plaatdikte		Afmetingen			
			Min.	Max.	D ø	H ø	P	L
113541	M 4	6,0	0,5	3,0	5,9	7,0	0,9	10,0
113542	M 5	7,0	0,5	3,0	6,9	8,0	0,9	11,5
113543	M 6	9,0	0,5	3,0	8,9	10,0	0,9	14,0
113544	M 8	11,0	0,5	3,0	10,9	12,0	0,9	15,5
113545	M 10	13,0	0,8	3,5	12,9	14,5	1,1	19,5

Alle afmetingen in mm; genoemde sterktewaarden zijn richtwaarden; technische wijzigingen voorbehouden.